

Parts Washing Compounds Selection Guide



Box 275 GRANDVILLE, MI 49468-0275
 PHONE: (616) 534-6103 FAX: (616) 534-0920
 EMAIL: SUPPORT@PROGRESSCHEMICAL.COM
www.progresschemical.com

LIQUID COMPOUND	METAL SAFETY	APPLICATION	CLEANING/ SOIL TYPE	INHIBIT	pH 1%	CONCENTRATION & TEMPERATURE
50-R	All	Soak/Spray	---	Ferrous	9.1	1 -5 oz/gal Below 160
1700	All	Spray/Soak	Oxide Removal	---	4.5	1 - 2 oz/gal 120-130
L-351E	Ferrous	Spray	Stable Oils	Ferrous	12.6	2 -3 oz/gal 120-160
L-360	Alum., Zinc, Steel	Spray	Oils/Particulate	---	11.6	1-4 oz/gal 120-160
L-372	Alum., Zinc, Steel	Soak	Oils/Particulate	Nonferrous	10.4	2 -8 oz/gal 120-135
DF-380	Ferrous	Soak/Ultrasonic	Oils/Particulate	---	12.2	3 -6 oz/gal 140-170
L-393	Ferrous	Spray	Oil/Smut/Scale	---	12.7	4 -12 oz/gal 120-160
L-590	Ferrous	Spray/Soak	Oil, Smut, Scale	---	13.0	5-16 oz/gal 120-170
L-737	All Metals	High Pressure Spray	Oils/Particulate	Ferrous	9.7	2 -3 oz/gal 150-180
T-220	All Metals	Soak/Turbo	Oils/Particulate	---	11.0	5% 110-130
T-230	All Metals	Spray	Oils/Particulate	---	11.0	4-8% 135-140
1831	All Metals	Ultrasonic	Oxides / Smut	---	4.8	9 oz/gal 130-140
1852	All Metals	Ultrasonic	Oxides / Smut	---	4.5	9 oz/gal 140-160
MP-222	Ferrous	Spray/Soak	---	Ferrous	9.7	2 - 4 oz/gal 70-180
900b	All Metals	Spray/Soak	---	Nonferrous	9.4	1-1/2 to 2 oz/gal
Pro-Hib 4700 B	Ferrous	Spray/Soak	Oils/Particulate	Ferrous	12.3	6-12 oz/gal 140-160
POWDER COMPOUND	METAL SAFETY	APPLICATION	CLEANING/ SOIL TYPE	INHIBIT	pH 1%	CONCENTRATION & TEMPERATURE
518	Ferrous	Spray	Oils/Particulate	Ferrous	12.5	1-2 oz/gal 120-160
521-A	Ferrous	Spray	Oils/Particulate	---	12	4-8 oz/gal 160-190
611-E	All, Esp. Brass	Soak	Oils/Particulate	Nonferrous	11.2	1-4 oz/gal 140-160
660	Alum, Zinc, Steel	Spray	Oils/Particulate	Alum., Zinc	10	1-3 oz/gal 150-170
AD-550	Ferrous	Spray/Soak	Oil, Smut, Scale	Ferrous	13.2	4-12 oz/gal 140-190
AD-593	Ferrous	Spray	Rust, Smut, Scale	Ferrous	13.0	4-12 oz/gal 120-160

Our Selection Guide gives a general overview of our product line. It is not all inclusive nor does it take all factors into consideration. Please refer to our Product Application Guides, individual Product Sheets, and Material Safety DataSheets for additional information. Please call us for additional technical assistance. Blue signifies primary applications.

An ISO 9001-2000 Registered Company