

540 Cleaning & Deburring Compound



540 is an alkaline cleaning system. It contains potent wetting and dispersing agents coupled with a refined alkaline build. This high detergency aids in mass finishing operations by:

- Effectively removing oily soils and particulate
- Rapid deburring
- Promotes optimum color and finishes
- Keeps media clean
- Excellent rinsing properties

For vibratory and rotary barrel finishing operations use 2 to 4 ounces per gallon of water. The concentration requirements will vary depending on nature of parts, nature of alloy, mass to water ratios, types of media used (if any), soil conditions, cycle time requirements, equipment used, and finish desired.

HANDLING AND STORAGE INSTRUCTIONS

This product poses no fire hazards. Highly alkaline product. Avoid contact with skin eyes and clothing. Use good industrial hygiene practices such as wearing chemical safety goggles, rubber gloves, impermeable apron, rubber boots and other protective measures as necessary to prevent personal contact with product. In case of contact with skin or eyes, flush with water for 15 minutes and contact physician immediately. Remove contaminated clothing and launder before reuse. Store in properly labeled closed containers in cool dry place and rotate stock. When stored as above, shelf life is a minimum of 2 years.

Refer to our Material Safety Data Sheet for additional information.

Rev. 12/03

PHYSICAL PROPERTIES

Appearance	Off white powder
pH @ 1 % Solution	12.1
Solubility in Water	Excellent
Foaming Action	Controlled
Rinsing Action	Excellent
Odor	Mild
Metal Safety	Ferrous & most nonferrous

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 50 years experience. Our company has been certified to ISO 9001:2000 Quality Standards.

USAGE & DILUTION



INSTRUCTIONS

3015 Dormax S.W. Grandville, MI 49418
Phone (616-534-6103 Fax: 534-0920
www.progresschemical.com